















	DN	inch	size	mm	mm	bar	psi	bar	psi	mm	kg/m	
												
616 930 010	10	3/8"	-06	17,4	22,0	500	7.250	2.100	30.450	120	0,81	UF + 671 411 010
616 930 012	12	1/2"	-08	20,8	25,2	470	6.815	1.950	28.280	160	0,94	UF + 671 411 012
616 930 016	16	5/8"	-10	24,3	28,8	410	5.945	1.800	26.100	210	1,13	UF + 671 411 016
616 930 019	19	3/4"	-12	28,1	32,5	375	5.435	1.600	23.200	260	1,49	UF + 671 411 019
616 930 025	25	1"	-16	35,4	40,5	327	4.740	1.350	19.580	310	1,99	UF + 671 411 025
616 930 031	31	1 1/4"	-20	41,8	46,5	240	3.480	1.100	15.950	410	2,38	UF + 671 411 031

Beispielhafte Layline:

 Exovation TPX DN10 - 3/8" - WP 500 BAR (7.250 PSI) 

Seele:

Spez. synthetisches Gummi

Druckträger:

3 hochzugfeste Stahldrahtgeflechte

Decke:

Spez. synthetisches Gummi

Anwendung:

Hochdruckschlauch für Hydraulikflüssigkeiten, Mineralöle und Treibstoffe

Sicherheitsfaktor:

1 : 4

Temperaturbereich:

- 40° C / + 100° C || kurzzeitig: + 125° C

Ozonbeständigkeit:

Nach EN 27326, 150 h

Abriebbeständigkeit:

Nach EN ISO 6945, 0,70 g

Tube:

Synthetic rubber

Reinforcement:

3 high tensile steel braids

Cover:

Synthetic rubber

Application:

High pressure hose for hydraulic fluids, mineral oils and diesel fuels.

Safety factor:

1 : 4

Temperature range:

- 40° F / + 212° F || short-term: + 257° F

Ozone resistance:

Acc. to EN 27326, 150 h

Abrasion resistance:

Acc. to EN ISO 6945, 0,70 g